

Milesight IP Horn Speaker with Build in Mic 15W

Key Features

- ▶ Two-Way Intercom Communication.
- ▶ 48K OPUS, AEC, AGC, ANR.
- ▶ Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP.
- ▶ Compatible with IP Camera VMS via ONVIF.
- ▶ HTTP Control, Alarm in, Schedule.
- ▶ 15W Amplifier, PoE Power Supply.
- ▶ Built-in MIC.



	Model	MS-WS15P
Audio	Codec	OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
	Built-in Microphone	Support
Speaker	Max SPL	113dB
	Frequency Response	300Hz~8KHz
	Frequency Range	500-2KHZ ±10dB, 400-12KHZ ±20dB
	Harmonic Distortion	0.1@1kHz
	Signal to Noise Ratio	91dB
Network	Security	Password protection, IP address filtering, Digest authentication, firewall
	Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
	Network Interface	10/100 Base-TX, RJ45
	VoIP	Support SIP protocol for VoIP systems integration, integrated with SIP/PBX. 2 SIP Accounts, SIP Direct IP Call, RTP Multicast, Codec: OPUS, MP3, G.722, PCMU, PCMA
Amplifier	Amplifier Description	Built-in 15W Amplifier
General	Operating Temperature	-30℃~60℃
	Operating humidity	5%~85%
	Material	ABS (IP66 water-proof)
	Rate Power	15W
	Power Supply	PoE or DC 12V/24V
	Connector	Alarm in, Audio in, DC Power, PoE
	Installation	Wall Mounted
	Dimensions	225*165*240mm
	Net Weight	1.3 KG
	Warranty	2 years

