Cost-effective solution for single-path connectivity.

Housing Material:	ABS Plastic – Green
Dimensions:	108mm (h) x 15.5mm (d) x 80mm (w)
Weight:	80g
Operating Environment:	Operating Temperature: 0 - 50 °C Operating Humidity: 15% to 85% non-condensing
Communication Options:	Dual SIM 4G CAT M1
Supported 4G LTE Bands:	CAT M1 – B3(1800), B28(700)
Antenna:	1 x Triple Band 4G
Power:	8-15V DC Terminal Supply Standby Consumption: 0.04A @ 13.8VDC Transmitting Consumption: 0.19A @ 13.8VDC
Dial Capture Modem:	Alarm Panel Dialler supporting DTMF tone dialling and line fault detection
Serial Port:	High-speed RS232 Interface
Auxiliary Input:	3 x 24hr inputs – state change detection every second EOL 3.3K
Auxiliary Output:	3 x Open-Collector outputs @ 50mA (max) Function control using Atlas Web Portal and/or Pocket Secure Mobile App
Data Security:	AES128 Encryption, ISO27001:2022
Mounting:	Magnets DIN Rail Mount Kit (Sold Separately)
Warranty:	2 years (from date of activation)

Contact Us:

T: 1300 55 66 43
E: sales@permaconn.com
W: permaconn.com