Multi-path security connectivity with the option of IP connectivity,

Housing Material:	ABS Plastic – Green
Dimensions:	110 mm (h) x 25mm (d) x 80mm (w)
Weight:	120g
Operating Environment:	Operating Temperature: 0 - 50 °C Operating Humidity: 15% to 85% non-condensing
Communication Options:	Dual SIM 4G + Ethernet (10/100BASE-T)
Supported 4G LTE Bands:	B1(2100), B3(1800), B4(1700-2100), B5(850), B7(2600), B8(900), B28(700), B40(2300)
Antenna:	1 x Triple Band 4G
IP Interface:	WAN Interface (10/100BASE-T) Supports Static or Dynamic IP Network Configuration using Atlas Web Portal
Power:	8-15V DC Terminal Supply Standby Consumption: 0.08A @ 13.8VDC Transmitting Consumption: 0.19A @ 13.8VDC
Dial Capture Modem:	Alarm Panel Dialler supporting DTMF tone dialling and line fault detection 2400 Baud Modem for Atlas Panel Remote U/L
Serial Port:	High-speed RS232 Interface
Auxiliary Input:	3 x 24hr inputs – state change detection every second EOL 3.3K
Auxiliary Output:	3 x Open-Collector outputs @ 50mA (max) Function control using Atlas Web Portal and/or Pocket Secure Mobile App
Data Security:	AES128 Encryption, ISO27001:2022
Mounting:	Magnets DIN Rail Mount Kit (Sold Separately)
Warranty:	2 years (from date of activation)
Approvals:	RCM, RoHS

Contact Us:

T: 1300 55 66 43
E: sales@permaconn.com
W: permaconn.com