

BioMini Slim 2

Ultra-slim FAP20 Authentication Scanner



BioMini Slim 2 is FAP20 certified fingerprint scanner featuring an array of cutting-edge technologies. Along with its 13.5mm slim optical sensor, BioMini Slim 2 features Suprema's proprietary Multi-dynamic Range(MDR) technology, FBI PIV and Mobile ID FAP20 compliance and Android device support. BioMini Slim 2 also provides developers more physical flexibility with its reduced form factor and the ultra-slim optical sensor ensures robust operation over time. BioMini Slim provides new and advanced Live Finger Detection(LFD) technology by applying a machine learning method that analyzes and categorizes image patterns according to optical characteristics.



BioMini Slim 2

Ultra-slim FAP20 Authentication Scanner

FEATURES



· World's slimmest FAP 20 optical sensor



· FBI PIV and FBI Mobile ID FAP20 certificates
· Image compression standard: WSQ



· Capturing high-quality fingerprint images even when the finger is dry & wet.
· Operates under direct sunlight up to 100,000 LUX



· Live Fingerprint Detection (LFD) Technology
· Distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film and more



· Easy Integration
· BioMini SDK for easy application development
· Android, MS Windows & Linux compatible
· Multi-threaded code design for multi-core CPU utilization



· No need to type in a password
· Instant login by touching your finger

SPECIFICATIONS

Sensor	Image Quality Standards	FBI PIV / FBI Mobile ID FAP20
	Live Finger Detection	O
	Sensor Type	Optical
	Resolution	500 ppi
	Gray Scale	256 level
	Platen Size (W x L mm)	16.5 x 21.0
	Sensing Area (W x H mm)	15.24 x 20.32
H/W	Image Size (W x H pixels)	300 x 400
	Interface	USB 2.0 High Speed
	Operating Temperature(°C)	-10~50°C
	Operating humidity	0 ~ 90% RH
	Ingress Protection	IP65 (Sensor Surface)
	Dimensions (W x L x Hmm)	72.8 X 40.7 X 18.5
	Weight (Kg)	91g
S/W	Windows	Windows XP, Vista, 7, 8, 8.1, 10 32/64bit
	Linux	Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64bit
	Android Android 4.1(Jelly Bean)and Above	O
	Image Format	RAW, BMP, WSQ, ISO 19794-4
	Template Type	Suprema, ISO19794-2, ANSI-378
Certification	CE	O
	FCC	O
	KC	O
	RoHS	O
	UL	X
	USB-IF	X
	CB	O
	IEC62471	O
	WEEE	O
	REACH	O
	WHQL	O

suprema
SECURITY & BIOMETRICS

Suprema ID Inc.

#305~308, 3F, Building A, Tera Tower 2, 201 Songpa-daero, Songpa-gu, Seoul, Republic of Korea

T +82 31 710 5629 E sales_id@supremainc.com www.suprema-id.com

©2020 Suprema ID Inc. Suprema and identifying product names and numbers herein are registered trade marks of Suprema ID Inc. All non-Suprema brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice. [SUPREMAID-DHL-BMS2-EN-REV06]