



A Solenis Company

Safety Data Sheet

TASKI REVEAL

Revision: 2024-01-25

Version: 01.1

SECTION 1: Identification of the substance/mixture and supplier

1.1 Product identifier

Product name: TASKI REVEAL

1.2 Recommended use and restrictions on use

Identified uses:

Floor cleaner

Restrictions of use:

Uses other than those identified are not recommended

1.3 Details of the supplier

Diversey Australia Pty. Limited
Unit 8, 55 Newton Road, Wetherill Park, NSW, 2164
1-7 Bell Grove, Braeside, VIC 3195
Telephone: 1800 647 779 (toll free)
Email: aucustserv@diversey.com
Website: diversey.com.au

1.4 Emergency telephone number

Seek medical advice (show the label or safety data sheet where possible)
Call 1800 033 111 (24hrs)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable liquids, Category 4
Serious eye damage, Category 1
Skin irritation, Category 2

2.2 Label elements



Signal word: Danger

Hazard statements:

H227 - Combustible liquid.
H315 - Causes skin irritation.
H318 - Causes serious eye damage.

Prevention statement(s):

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P235 - Keep cool.
P264 - Wash face, hands and any exposed skin thoroughly after handling.
P280 - Wear protective gloves, protective clothing and eye or face protection.

Response statement(s):

P332 + P313 - If skin irritation occurs: Get medical advice or attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 - Immediately call a POISON CENTRE, doctor or physician.
P321 - Specific treatment (see supplemental first aid instructions on this label).
P362 + P364 - Take off contaminated clothing and wash it before reuse.

Storage statement(s):

P403 - Store in a well-ventilated place.

Disposal statement(s):

P501 - Dispose of unused content as chemical waste.

2.3 Other hazards

No other hazards known.

2.4 Classification diluted product:

Recommended maximum concentration (% w/w): 2.44

Not classified as hazardous

SECTION 3: Composition/information on ingredients**3.1 Substances / Mixtures**

Ingredient(s)	CAS#	EC number	Weight percent
2-aminoethanol	141-43-5	205-483-3	3-10
2-butoxyethanol	111-76-2	203-905-0	1-3
sodium xylene sulphonate	1300-72-7	215-090-9 / 701-037-1	1-3

Non-hazardous ingredients are the remainder and add up to 100%.

Workplace exposure limit(s), if available, are listed in subsection 8.1.

SECTION 4: First aid measures**4.1 Description of first aid measures****Inhalation:**

Get medical attention or advice if you feel unwell.

Skin contact:

Wash skin with plenty of lukewarm, gently flowing water. If skin irritation occurs: Get medical advice or attention.

Eye contact:

Hold eyelids apart and flush eyes with plenty of lukewarm water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE, doctor or physician.

Ingestion:

Rinse mouth. Immediately drink 1 glass of water. Never give anything by mouth to an unconscious person. Get medical attention or advice if you feel unwell.

Self-protection of first aider:

Consider personal protective equipment as indicated in subsection 8.2.

First aid facilities:

Eyewash facilities should be considered in a workplace where necessary.

4.2 Most important symptoms and effects, both acute and delayed**Inhalation:**

No known effects or symptoms in normal use.

Skin contact:

Causes irritation.

Eye contact:

Causes severe or permanent damage.

Ingestion:

No known effects or symptoms in normal use.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

Poison Information Center:

Call 13 11 26 (Australia Wide).

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Carbon dioxide. Dry powder. Water spray jet. Fight larger fires with water spray jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

No special hazards known.

5.3 Advice for firefighters

As in any fire, wear self contained breathing apparatus and suitable protective clothing including gloves and eye/face protection.

5.4 Hazchem code

None allocated

SECTION 6: Accidental release measures

TASKI REVEAL

6.1 Personal precautions, protective equipment and emergency procedures

Turn off all sources of ignition. Ventilate the area. Wear suitable protective clothing. Wear eye/face protection. Repeated or prolonged contact: Wear suitable gloves.

6.2 Environmental precautions

Dilute with plenty of water. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up

Dyke to collect large liquid spills. Absorb with liquid-binding material (sand, diatomite, universal binders). Do not place spilled materials back into the original container. Collect in closed and suitable containers for disposal.

6.4 Reference to other sections

For personal protective equipment see subsection 8.2. For disposal considerations see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Measures to prevent fire and explosions:**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use non-sparking tools.

Measures required to protect the environment:

For environmental exposure controls see subsection 8.2.

Advices on general occupational hygiene:

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not mix with other products unless advised by Diversey. Wash face, hands and any exposed skin thoroughly after handling. Take off contaminated clothing. Wash contaminated clothing before reuse. Avoid contact with skin and eyes. Use only with adequate ventilation. See chapter 8.2, Exposure controls / Personal protection.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local and national regulations. Store in a well-ventilated place. Store in a closed container. Keep only in original packaging. Keep cool. Keep away from heat and direct sunlight.

For conditions to avoid see subsection 10.4. For incompatible materials see subsection 10.5.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Workplace exposure limits**

Air limit values, if available:

Ingredient(s)	Long term value(s) (TWA)	Short term value(s) (STEL)	Peak value(s)
2-aminoethanol	3 ppm 7.5 mg/m ³	6 ppm 15 mg/m ³	
2-butoxyethanol	20 ppm 96.9 mg/m ³	50 ppm 242 mg/m ³	

Biological limit values, if available:

8.2 Exposure controls

The following information applies for the uses indicated in subsection 1.2 of the Safety Data Sheet.

If available, please refer to the product information sheet for application and handling instructions.

Normal use conditions are assumed for this section.

Recommended safety measures for handling the undiluted product:

Covering activities such as filling and transfer of product to application equipment, flasks or buckets

Appropriate engineering controls:

If the product is diluted by using specific dosing systems with no risk of splashes or direct skin contact, the personal protection equipment as described in this section is not required.

Appropriate organisational controls:

Avoid direct contact and/or splashes where possible. Train personnel.

Personal protective equipment**Eye / face protection:**

Safety glasses or goggles (AS/NZS 1337.1).

Hand protection:

Chemical-resistant protective gloves (AS/NZS 2161.10). Verify instructions regarding permeability and breakthrough time, as provided by the gloves supplier. Consider specific local use conditions, such as risk of splashes, cuts, contact time and temperature.

Suggested gloves for prolonged contact: Material: butyl rubber Penetration time: ≥ 480 min Material thickness: ≥ 0.7 mm

Suggested gloves for protection against splashes: Material: nitrile rubber Penetration time: ≥ 30 min

TASKI REVEAL

	Material thickness: ≥ 0.4 mm
	In consultation with the supplier of protective gloves a different type providing similar protection may be chosen.
Body protection:	Wear chemical-resistant clothing and boots in case direct dermal exposure and/or splashes may occur (EN 14605).
Respiratory protection:	No special requirements under normal use conditions.
Environmental exposure controls:	No special requirements under normal use conditions.
<i>Recommended safety measures for handling the <u>diluted</u> product:</i>	
Recommended maximum concentration (% w/w): 2.44	
Appropriate engineering controls:	No special requirements under normal use conditions.
Appropriate organisational controls:	No special requirements under normal use conditions.
Personal protective equipment	
Eye / face protection:	No special requirements under normal use conditions.
Hand protection:	No special requirements under normal use conditions.
Body protection:	No special requirements under normal use conditions.
Respiratory protection:	No special requirements under normal use conditions.
Environmental exposure controls:	No special requirements under normal use conditions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

	Method / remark
Physical state: Liquid	
Colour: Clear , Purple	
Odour: Product specific	
Odour threshold: Not applicable	
pH: ≥ 11.5 (neat)	ISO 4316
Melting point/freezing point (°C): Not determined	Not relevant to classification of this product
Initial boiling point and boiling range (°C): Not determined	
Flammability (liquid): Combustible.	
Flash point (°C): Not determined	
Sustained combustion: Not applicable. (UN Manual of Tests and Criteria, section 32, L.2)	
Evaporation rate: Not determined	
Flammability (solid, gas): Not applicable to liquids	
Lower and upper explosion limit/flammability limit (%): Not determined	
Vapour pressure: Not determined	
Relative density: ≈ 1.01 (20 °C)	
Relative vapour density: No data available.	
Particle characteristics: No data available.	
Solubility in / Miscibility with water: Fully miscible	
Partition coefficient: n-octanol/water No information available.	
Substance data, partition coefficient n-octanol/water (log Kow): see subsection 12.3	
Autoignition temperature: Not determined	
Decomposition temperature: Not applicable.	
Viscosity: Not determined	
Explosive properties: Not explosive. Vapours may form explosive mixtures with air.	
Oxidising properties: Not oxidising.	
9.2 Other information	
Surface tension (N/m): Not determined	
Corrosion to metals: Not corrosive	

SECTION 10: Stability and reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal storage and use conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known under normal storage and use conditions.

10.4 Conditions to avoid

None known under normal storage and use conditions.

10.5 Incompatible materials

None known under normal use conditions.

10.6 Hazardous decomposition products

None known under normal storage and use conditions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture data:

Relevant calculated ATE(s):

ATE - Oral (mg/kg): >2000

ATE - Dermal (mg/kg): >2000

ATE - Inhalatory, vapours (mg/l): >20

Substance data, where relevant and available, are listed below:

Acute toxicity

Acute oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)
2-aminoethanol	LD ₅₀	1089	Rat	OECD 401 (EU B.1)	
2-butoxyethanol	LD ₅₀	1746	Rat	ATE - Acute Toxicity Estimate	
sodium xylene sulphonate	LD ₅₀	> 7200	Rat	OECD 401 (EU B.1)	

Acute dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)
2-aminoethanol	LD ₅₀	2504	Rabbit	OECD 402 (EU B.3)	
2-butoxyethanol	LD ₅₀	6411		Method not given	
sodium xylene sulphonate	LD ₅₀	> 2000	Rabbit	OECD 402 (EU B.3)	

Acute inhalative toxicity

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
2-aminoethanol	LC ₅₀	> 1.4 No mortality observed	Rat	Method not given	4
2-butoxyethanol	LC ₅₀	> 2 (mist) No mortality observed	Rat	Method not given	4
sodium xylene sulphonate	LC ₀	> 6.41 (mist) No mortality observed	Rat	OECD 403 (EU B.2)	4

Irritation and corrosivity

Skin irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
2-aminoethanol	Corrosive	Rabbit	OECD 404 (EU B.4)	
2-butoxyethanol	Irritant	Rabbit	OECD 404 (EU B.4)	24; 48; 72 hour(s)
sodium xylene sulphonate	Mild irritant	Rabbit	OECD 404 (EU B.4)	

Eye irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
2-aminoethanol	Severe damage	Rabbit	OECD 405 (EU B.5)	

TASKI REVEAL

2-butoxyethanol	Irritant	Rabbit	OECD 405 (EU B.5)	24; 48; 72 hour(s)
sodium xylene sulphonate	Irritant	Rabbit	OECD 405 (EU B.5)	

Respiratory tract irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
2-aminoethanol	Irritating to respiratory tract		Method not given	
2-butoxyethanol	No data available			
sodium xylene sulphonate	No data available			

Sensitisation

Sensitisation by skin contact

Ingredient(s)	Result	Species	Method	Exposure time (h)
2-aminoethanol	Not sensitising	Guinea pig	OECD 406 (EU B.6) / GPMT	
2-butoxyethanol	Not sensitising	Guinea pig	OECD 406 (EU B.6) / GPMT	
sodium xylene sulphonate	Not sensitising	Guinea pig	OECD 406 (EU B.6) / GPMT	

Sensitisation by inhalation

Ingredient(s)	Result	Species	Method	Exposure time
2-aminoethanol	No data available			
2-butoxyethanol	No data available			
sodium xylene sulphonate	No data available			

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Mutagenicity

Ingredient(s)	Result (in-vitro)	Method (in-vitro)	Result (in-vivo)	Method (in-vivo)
2-aminoethanol	No evidence for mutagenicity, negative test results	OECD 471 (EU B.12/13) OECD 473 OECD 476 (Mouse lymphoma)	No evidence for mutagenicity, negative test results	OECD 474 (EU B.12)
2-butoxyethanol	No evidence for mutagenicity, negative test results	OECD 471 (EU B.12/13) OECD 476 (Chinese Hamster Ovary)	No evidence for mutagenicity, negative test results	OECD 474 (EU B.12)
sodium xylene sulphonate	No evidence for mutagenicity, negative test results	OECD 473	No evidence for mutagenicity, negative test results	OECD 474 (EU B.12)

Carcinogenicity

Ingredient(s)	Effect
2-aminoethanol	No evidence for carcinogenicity, weight-of-evidence
2-butoxyethanol	No evidence for carcinogenicity, negative test results
sodium xylene sulphonate	No evidence for carcinogenicity, negative test results

Toxicity for reproduction

Ingredient(s)	Endpoint	Specific effect	Value (mg/kg bw/d)	Species	Method	Exposure time	Remarks and other effects reported
2-aminoethanol	NOAEL	Developmental toxicity	> 75	Rabbit	OECD 414 (EU B.31), oral	6 - 15 day(s)	No evidence for developmental toxicity No evidence for reproductive toxicity
2-butoxyethanol			No data available				
sodium xylene sulphonate	NOAEL	Teratogenic effects	> 936	Rat	Non guideline test		

Repeated dose toxicity

Sub-acute or sub-chronic oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
2-aminoethanol	NOAEL	300	Rat		75	
2-butoxyethanol		No data available				
sodium xylene sulphonate	NOAEL	763 - 3534	Rat	OECD 408 (EU B.26)	90	

Sub-chronic dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
---------------	----------	--------------------	---------	--------	----------------------	--------------------------------------

TASKI REVEAL

2-aminoethanol		No data available			
2-butoxyethanol		No data available			
sodium xylene sulphonate	NOAEL	> 440		OECD 411 (EU B.28)	90

Sub-chronic inhalation toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
2-aminoethanol		No data available				
2-butoxyethanol		No data available				
sodium xylene sulphonate		No data available				

Chronic toxicity

Ingredient(s)	Exposure route	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time	Specific effects and organs affected	Remark
2-aminoethanol			No data available					
2-butoxyethanol			No data available					
sodium xylene sulphonate	Oral		No data available	Rat	OECD 453 (EU B.33)	24 month(s)	No adverse effects observed	

STOT-single exposure

Ingredient(s)	Affected organ(s)
2-aminoethanol	Respiratory tract
2-butoxyethanol	No data available
sodium xylene sulphonate	No data available

STOT-repeated exposure

Ingredient(s)	Affected organ(s)
2-aminoethanol	No data available
2-butoxyethanol	No data available
sodium xylene sulphonate	No data available

Aspiration hazard

Substances with an aspiration hazard (H304), if any, are listed in section 3.

Potential adverse health effects and symptoms

Effects and symptoms related to the product, if any, are listed in subsection 4.2.

SECTION 12: Ecological information

12.1 Toxicity

No data is available on the mixture.

Substance data, where relevant and available, are listed below:

Aquatic short-term toxicity

Aquatic short-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
2-aminoethanol	LC ₅₀	349	<i>Cyprinus carpio</i>	OECD 203, semi-static	96
2-butoxyethanol	LC ₅₀	> 100	<i>Oncorhynchus mykiss</i>	OECD 203, static	96
sodium xylene sulphonate	LC ₅₀	> 1000	<i>Oncorhynchus mykiss</i>	Method not given	96

Aquatic short-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
2-aminoethanol	EC ₅₀	27.04	<i>Daphnia magna</i> Straus	OECD 202, static	48
2-butoxyethanol	EC ₅₀	> 100	<i>Daphnia magna</i> Straus	OECD 202, static	48
sodium xylene sulphonate	EC ₅₀	> 1000	<i>Daphnia</i>	Method not given	48

TASKI REVEAL

Aquatic short-term toxicity - algae

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
2-aminoethanol	EC ₅₀	2.8	<i>Selenastrum capricornutum</i>	OECD 201 (EU C.3)	72
2-butoxyethanol	EC ₅₀	> 100	<i>Pseudokirchneriella subcapitata</i>	OECD 201, static	72
sodium xylene sulphonate	EC ₅₀	> 230	Not specified	EPA OPPTS 850.5400	96

Aquatic short-term toxicity - marine species

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (days)
2-aminoethanol		No data available			
2-butoxyethanol		No data available			
sodium xylene sulphonate		No data available			

Impact on sewage plants - toxicity to bacteria

Ingredient(s)	Endpoint	Value (mg/l)	Inoculum	Method	Exposure time
2-aminoethanol	EC ₅₀	> 1000	Activated sludge	DIN EN ISO 8192-OECD 209-88/302/EEC	3 hour(s)
2-butoxyethanol	EC ₀	700	<i>Pseudomonas putida</i>	Method not given	16 hour(s)
sodium xylene sulphonate	E _r C ₅₀	> 1000	Activated sludge	OECD 209	3 hour(s)

Aquatic long-term toxicity

Aquatic long-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
2-aminoethanol	NOEC	1.2	<i>Oryzias latipes</i>	OECD 210	30 day(s)	
2-butoxyethanol	NOEC	> 100	<i>Danio rerio</i>	OECD 204	21 day(s)	
sodium xylene sulphonate		No data available				

Aquatic long-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
2-aminoethanol	NOEC	0.85	<i>Daphnia magna</i>	OECD 202	21 day(s)	
2-butoxyethanol	NOEC	100	<i>Daphnia magna</i>	OECD 211	21 day(s)	
sodium xylene sulphonate		No data available				

Aquatic toxicity to other aquatic benthic organisms, including sediment-dwelling organisms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw sediment)	Species	Method	Exposure time (days)	Effects observed
2-aminoethanol		No data available				

Terrestrial toxicity

Terrestrial toxicity - soil invertebrates, including earthworms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
2-aminoethanol		No data available				

Terrestrial toxicity - plants, if available:

Terrestrial toxicity - birds, if available:

Ingredient(s)	Endpoint	Value	Species	Method	Exposure time (days)	Effects observed
2-aminoethanol		No data available				

Terrestrial toxicity - beneficial insects, if available:

TASKI REVEAL

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
2-aminoethanol		No data available				

Terrestrial toxicity - soil bacteria, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
2-aminoethanol		No data available				

12.2 Persistence and degradability

Abiotic degradation

Abiotic degradation - photodegradation in air, if available:

Abiotic degradation - hydrolysis, if available:

Abiotic degradation - other processes, if available:

Biodegradation

Ready biodegradability - aerobic conditions

Ingredient(s)	Inoculum	Analytical method	DT ₅₀	Method	Evaluation
2-aminoethanol		DOC reduction	> 90 % in 21 day(s)	OECD 301A	Readily biodegradable
2-butoxyethanol		CO ₂ production	90.4 % in 28 day(s)	OECD 301B	Readily biodegradable
sodium xylene sulphonate	Activated sludge, aerobe	CO ₂ production	99.8 % in 28 day(s)	OECD 301B	Readily biodegradable

Ready biodegradability - anaerobic and marine conditions, if available:

Degradation in relevant environmental compartments, if available:

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Ingredient(s)	Value	Method	Evaluation	Remark
2-aminoethanol	- 1.91	OECD 107	No bioaccumulation expected	
2-butoxyethanol	0.81	OECD 107	Low potential for bioaccumulation	
sodium xylene sulphonate	-3.12	Method not given	No bioaccumulation expected	

Bioconcentration factor (BCF)

Ingredient(s)	Value	Species	Method	Evaluation	Remark
2-aminoethanol	No data available				
2-butoxyethanol	No data available				
sodium xylene sulphonate	No data available				

12.4 Mobility in soil

Adsorption/Desorption to soil or sediment

Ingredient(s)	Adsorption coefficient Log Koc	Desorption coefficient Log Koc(des)	Method	Soil/sediment type	Evaluation
2-aminoethanol	0.067		Model calculation		Potential for mobility in soil, soluble in water Adsorption to solid soil phase is not expected
2-butoxyethanol	No data available				Potential for mobility in soil, soluble in water
sodium xylene sulphonate	No data available				

12.5 Other adverse effects

No other adverse effects known.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste from residues / unused products:

The concentrated contents or contaminated packaging should be disposed of by a certified handler or according to the site permit. Release of waste to sewers is discouraged. The cleaned packaging material is suitable for energy recovery or recycling in line with local legislation.

TASKI REVEAL

Empty packaging**Recommendation:**

Dispose of observing national or local regulations.

Suitable cleaning agents:

Water, if necessary with cleaning agent.

SECTION 14: Transport information**ADG, IMO/IMDG, ICAO/IATA****14.1 UN number or ID number:** Non-dangerous goods**14.2 UN proper shipping name:** Non-dangerous goods**14.3 Transport hazard class(es):** Non-dangerous goods**14.4 Packing group:** Non-dangerous goods**14.5 Environmental hazards:** Non-dangerous goods**14.6 Special precautions for user:** Non-dangerous goods**14.7 Maritime transport in bulk according to IMO instruments:** Non-dangerous goods**Other relevant information:****Hazchem code:** None allocated**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Globally Harmonised System of Classification and Labelling of Chemicals (GHS) as published by Safework Australia.

Poison schedule

A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classification

Globally Harmonised System of Classification and Labelling of Chemicals (GHS) as published by Safework Australia.

Inventory listing(s)

Australian Inventory of Industrial Chemicals: All components are listed on the inventory, or are exempt.

Additional advice

- Does not contain added fragrance

SECTION 16: Other information

The information in this document is based on our best present knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally binding contract

SDS code: MS3100912**Version:** 01.1**Revision:** 2024-01-25**Reason for revision:**

This data sheet contains changes from the previous version in section(s): 2, 4, 6, 7, 8, 10, 14, 15

Additional information:

Respirators: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

Work practices - solvents: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

Exposure standards - Time Weighted Average (TWA) or Workplace Exposure Standard (WES) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

TASKI REVEAL

Personal protective equipment guidelines: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Health effects from exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Safety Data Sheet which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations and acronyms:

- ATE - Acute Toxicity Estimate
- AUH - Non GHS hazard statement
- DNEL - Derived No Effect Limit
- EC No. - European Community Number
- EC50 - effective concentration, 50%
- LC50 - Lethal Concentration, 50% / Median Lethal Concentration
- LD50 - Lethal Dose, 50% / Median Lethal dose
- NOAEL - No observed adverse effect level
- NOEL - No observed effect level
- OECD - Organisation for Economic Cooperation and Development
- PNEC - Predicted No Effect Concentration
- STOT-RE - Specific target organ toxicity (repeated exposure)
- STOT-SE - Specific target organ toxicity (single exposure)

End of Safety Data Sheet