SPC PSTN Module

VANDERBILT



SPC PSTN Module

Vanderbilt`s SPCN110 offers the ability to expand the SPC system with reporting and SMS functionality.

Key Features include:

communication

The communication module enables the control panel to communicate with PSTN networks. The SPCN110 primary or secondanry communication path for multievent alarm transmission to SIA/Contact ID standard receivers.

SMS Reporting

The SPC system can support up to 100 SMS numbers (SPC6xxx) each number can have a unique filter of which events are to be sent.

Easy mounting and configuration

The modem plugs directly onto the SPC controller main board removing the need for any additional wiring. All the module functions are configurable via the control panel.

Operations:







SPCN110

SPC PSTN Module





Technical Data

Functional	
Network connections	PSTN (analogue telephone network)
Power and Mechanical	
Operating current	Max.35 mA at 12 V DC (communication active)
Quiescent current	Max. 25 mA at 12 V DC
Mounting	Plug on module to SPC controller
Operating temperature	-10° ~ +50 °C
Dimensions	90 x 38 x 25 (PCB)
Weight	0.030 kg



Vanderbilt A6V10395217_b © Vanderbilt 2016 page 2

SPC PSTN Module

Ordering Data

Туре	Art. No.	Description	Weight*
Modem	V54550-B101-A100	SPCN110.000 PSTN module	0.030Kg


* Total weight of the product inclusive of the weight of its accessories and packaging.

Additional Ordering Data

Туре	Art. No.	Description
SPC Panels		
SPC6350.320-L1	V54541-C118-A100	SPC control panel, 16-512 zones, Ethernet, G5 metal housing
SPC6330.320-L1	V54541-C105-C100	SPC control panel, 8-512 zones, Ethernet, G3 metal housing
SPC5350.320-L1	V54541-C117-A100	SPC control panel, 16-128 zones, Ethernet, G5 metal housing
SPC5330.320-L1	V54541-C107-B100	SPC control panel, 8-128 zones, Ethernet, G3 metal housing
SPC5320.320-L1	V54541-C106-B100	SPC control panel, 8-128 zones, Ethernet, G2 metal housing
SPC4320.320-L1	V54541-C109-B100	SPC control panel, 8-32 zones, Ethernet, G2 metal housing
SPC4320.220-L1	V54541-C114-A100	SPC control panel, 8-32 zones, Ethernet, G2 housing with metal base and plastic cover
Keypads		
SPCK520.100-N	V54543-F115-A100	Compact Keypad with graphical display and audio
SPCK521.100-N	V54543-F116-A100	Compact Keypad with graphical display, card reader and audio
SPCK620.100	V54543-F110-A100	LCD keypad with graphical display
SPCK623.100	V54543-F111-A100	LCD keypad with graphical display, card reader and audio
SPCK420.100	V54543-F101-A100	LCD keypad with 2 x 16 characters
SPCK421.100	V54543-F102-A100	LCD keypad with 2 x 16 characters and integrated card reader
Expanders		
SPCE452.100	V54542-F107-A100	Expander with 8 outputs, back tamper
SPCE652.100	V54542-F106-A100	Expander with 8 inputs and 2 outputs, back tamper
SPCA210.100	V54547-A101-A100	2-door expander
SPCP432.300	V54545-C103-A100	Smart PSU with 2-door expander, G2-housing
SPCP433.300	V54545-C104-A100	Smart PSU with 2-door expander, G3-housing
SPCE110.100	V54542-F104-A100	Keyswitch expander with 2 LEDs and 3-position key switch
SPCE120.100	V54542-F105-A100	Indication expander with 16 LEDs, 4 function keys and integrated card reader
SPCW130.100	V54554-F101-B100	SiWay RF-expander
SPCP332.300	V54545-C102-A100	Smart PSU with 8 inputs and 2 outputs, G2-housing
SPCP333.300	S54545-C101-A100	Smart PSU with 8 inputs and 2 outputs, G3-housing
SPCP355.300	S54545-C105-A100	Smart PSU with 8 inputs and 6 outputs, G5 metal housing

Detectors		
PDM-I12	V54530-F114-A100	MAGIC PIR detector, 12m wide angle
PDM-I18	V54530-F106-A100	MAGIC PIR detector, 18 m wide angle
MK-1400	V54536-F101-A100	Magnetic contact

Accessories



VANDERBILT

VANDERBILT

© Vanderbilt 2016 page 3

SPCN110

SPC PSTN Module

IPAW8-10	V54538-F107-A100	Wireless personal alarm	
		SiWay remote control, white	
IRCW6-11	V54543-F109-A100	replaceable battery	
IPAW6-10	V54538-F108-A100	Wireless Personal Alarm Button	

Verification		
SPCV340.000	V54542-F108-B100	Audio expander with 4 inputs and 1 output
SPCV341.000	V54542-F109-B100	Audio expander with 4 inputs and 1 line output
SPCV310.000	V54542-F120-A100	Audio satellite
SPCV440.000	V54542-F118-A100	Combi audio expander for MAGIC motion detectors with 4 inputs and 1 output
SPCV410.000	V54542-F119-A100	Combi audio satellite for MAGIC motion detectors
CCMS2010-IR	S54561-C112-A100	1/2.7" 2MP Compact IP Camera PoE(LAN)
Access		
		Multi technology cord reader

AR6181-MX	6FL7170-8BK	Multi-technology card reader	
PP500-EM	V54501-F1-A1	Heavy-duty card and PIN reader	
AR6182-RX	6FL7170-8AE	Multi-technology card and PIN reader	



Learn more at www.vanderbiltindustries.com

Issued by Vanderbilt Clonshaugh Business and Technology Park Clonshaugh Dublin 17 Ireland www.vanderbiltindustries.com

© Vanderbilt 2016 Data and design subject to change without notice. Supply subject to availability. Document version: b Edition: 01.01.2016



Vanderbilt A6V10395217_b © Vanderbilt 2016 page 4 VANDERBILT